

High-End full-range speaker series!

The SC series is our newly developed high-end full range speaker series especially designed for high-end fixed installations and occasions. This series is equipped with customized Stagetone driver & woofer produced by famous UK brand Precision Devices. The neodymium driver STG-1.53NP with 72,2 mm voice coil is mounted on a constant directivity aluminum horn with 50x80° coverage pattern. The woofer STG-123FP offers excellent linear response well controlled down to 40Hz (SC-12 = 50Hz). The high woofers BL provides the required good punch. The Mid/High frequency range is extremely transparent and clear which regale you ear by plenty of instrumental details. The anti-scratching & water-resistant housing is equipped with suspension points for several different mounting applications. With our U-profile hanging kit, you will able to adjust the hanging angle properly to suit the different sound environment.

SC SERIES









- Crafted with the High-End components
- Designed for fixed installations
- 1100 W program power
- 550 W AES power
- Connecting panel with Neutrik NL4 sockets
- 8 Ohm Impedance
- 80° x 50° Coverage Pattern

SC-12	
30-12	
Model Name	SC-12
GS1 (EAN) CODE	4260318511728
System Type	2-Way 12"+1,5" Fullrange Speaker
Power Rating	550 W AES 1100 W program 2200 W peak
Frequency Range (+/- 3 dB)	50 Hz - 20 kHz
Coverage Pattern (hxv)	80°x50°
Sensitivity	98 dB 1w/1m
Maximum SPL	128 dB
Woofer	1 x STG-123FP
Driver	STG-1.53NP
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Suspension/Mounting	35 mm pole socket 15 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	610x361x377 mm



Order Code	GS1 (EAN) Code	Туре
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm















- Suitable for fixed installations
- 1200 W program power
- 600 W AES power
- 10 x M8 suspension points
- 1,4" compression driver with 3" voice coil
- 8 Ohm Impedance
- 80° x 50° horn design

Speci- fication	
SC-15	
Model Name	SC-15
GS1 (EAN) CODE	4260318511735
System Type	2-Way 15"+1,5" Fullrange Speaker
Power Rating	600 W AES 1200 W program 2400 W peak
Frequency Range (+/- 3 dB)	40 Hz - 20 kHz
Coverage Pattern (hxv)	80°x50°
Sensitivity	101 dB 1w/1m
Maximum SPL	136 dB
Woofer	1 x STG-153FP
Driver	STG-1.53NP
Nominal Impedance	8 Ohm
Input Connectors	2 x Neutrik NL4 Socket parallel 1+/1-
Suspension/Mounting	35 mm pole socket 15 x M8 suspension U-Profil-Base
Housing	Birch Multiplex
Coating	Anti-scratch Polyurethane coating
Dimensions (h/w/d)	700x431,5x436 mm
Net weight	34,0 kg



Order Code	GS1 (EAN) Code	Туре
STG-STD	4260318511032	Tripot Speaker Stand
KA-SP2-05	4260318510967	5 Meter Speaker cable 2x2,5qmm
KA-SP2-10	4260318510974	10 Meter Speaker cable 2x2,5qmm
KA-SP2-15	4260318510981	15 Meter Speaker cable 2x2,5qmm
KA-SP2-20	4260318510998	20 Meter Speaker cable 2x2,5qmm











SC Sizes















SC-SERIES















INLINE Marketing GmbH Bunsenstrasse 32 59229 Ahlen, Germany

Tel.+49 2382 7087-0Fax+49 2382 7087-25E-Mailsales@4-acoustic.comWebwww.4-acoustic.com